key features & benefits

 Powerful 4.25 HP, high-efficiency DC motor



 Intuitive LED with dual speed and incline toggle controls, audio input, speakers, USB port, reading rack/tablet holder and cup holders



- Simple design makes the 6000 treadmill easier and more efficient to assemble, service and relocate
- Contact and wireless heart-rate sensors are compatible with a variety of industry-leading monitors
- Low step-on height and rubber foot grips with durable full-commercial components on a space-saving commercial frame
- ✓ 60" x 20" premium lubricant-infused low-maintenance running belt with 1" reversible phenolic deck



- More than 20 exercise programs and integrated 2-speed personal fan
- Illuminated power-on switch with quick-connect safety clip
- The Smooth Deck Shock Absorption System with urethane suspension delivers a stable and flexible running surface designed to provide the ultimate comfort, reducing stress on knees and joints
- Zinc-dipped anti-corrosion coating for superior rust protection





M6 TREADMILL CIR-TM6000DC-C

Affordability meets durability in the M6 treadmill. Featuring high-quality, full commercial components on a space-saving frame, this treadmill is built for unparalleled reliability and energy efficiency.



technical specs

Product Weight: 302 lbs.

Running Surface: 60" x 20"

Width: 36" Length: 78"

heart-rate sensors

1 fitness test, 2 custom

rack/tablet holder

of daily use).

than PVC

Heart Rate Monitoring: Contact & telemetric

Display Feedback: Time, distance, heart-rate,

calories, speed, incline, calories/hour, pace

Keypad: Teflon keypad TPU lasts 25% longer

Programs: 20 programs, 1 target, 3 HRC,

Standard Features: Hand pulse, fan,

heart-rate receiver chest belt compatible,

Warranty: 10 years frame, 6 years motors &

parts, 2 years wearable items, 1 year labor in light commercial applications (up to 6 hours

4 quick keys for both speed & incline & reading

Display: 8 x 16 dot matrix console with

message window + HR status bar

Height: 57"

Motor: 4.25 HP, DC, high-efficiency Electrical: 120V, 20 amp dedicated NEMA 5-20 Certification: UL, CSA, CE & EU MEPS Rollers: 2.75"

Step-On Height: 7"

Belt: Premium lubricant-infused low maintenance running belt **Deck:** 60" x 20" running surface, with 1" reversible phenolic deck

Speed Range: 0.3 - 15.5 MPH Incline Range: 0 - 15% incline

User Weight: 400 lbs.

Transport Wheels: Easy-to-move with frontmounted dual wheels without elevating

Frame: Zinc-dipped, anti-corrosion coated heavy gauge steel







