

# STRENGTH EQUIPMENT



## MID ROW/LAT PULL DOWN BAT-LD-2

- Telescoping chest pad
- Dual handgrips
- Gas assisted seat
- Hold-down rollers
- Swiveling high pulley
- 200 lbs. weight stack



| Overall Weight | Weight Stack | Width | Depth | Height |
|----------------|--------------|-------|-------|--------|
| 505 lbs.       | 200 lb.      | 44"   | 61"   | 84"    |

### FEATURES AND SPECIFICATIONS

**Frame:** 2" x 4" and 1-1/2" x 3" 11 gauge (.120 wall) structural steel tube with 3/8" and 1/4" thick steel plate. Mounting plates with rubber feet protect floor and prevent the machine from sliding

**Finish:** Abrasive blasted and/or chemically treated frames are electrostatically powder coated ensuring maximum adhesion and durability

**Pivot Points:** Sealed bearings and oil impregnated bronze bushings operate on solid shafts to ensure a smooth movement and tight fit

**Cams:** Laser cut from 3/8" steel plate and offer starting point adjustment on applicable machines

**Weight Stack:** Precision machined solid steel weight plates with individual bushings travel on solid, chromed, guide rods to ensure ultra smooth operation. Heavy rubber suspension bumpers are used to absorb and reduce shock

**Foot Platforms:** 3/16" thick powder coated steel diamond plate to avoid slipping

**Pulleys:** Glass reinforced nylon operating on precision steel ball bearings

**Cables:** Nylon coated, lubricated, mil. spec. cable. 2000 lb. tensile strength. Pivoting cable ends with oil-impregnated bronze bushings promote long cable life

**Upholstery:** Contoured pads with lumbar support make a comfortable and well supported workout. Pads are double stitched and handcrafted from the finest materials available

**Seat Adjustments:** Adjustable seats are gas assisted and all telescoping pad adjustments use nylon sleeves to make Batca seat adjustments smooth and effortless

**Shroud:** Formed and powder coated steel weight stack guard is standard

**Warranty:** 10 years frame, 3 years parts, 6 months upholstery