

STRENGTH EQUIPMENT



BICEPS CURL

TSF-PPS-206

- Multi-grip handle design allows for underhand or overhand grip positions
- Pivot arm counter-balanced to 0 lb. at starting position
- Easy access gas assist seat adjustment
- Ergonomically designed arm rest for maximum support and comfort
- 150 lbs. steel weight stack with add-on weight system
- **Optional:** 200 lbs. weight stack



Overall Weight	Weight Stack	Width	Depth	Height
380 lbs.	150 lb.	43"	45"	57"
FEATURES AND SPECIFICATIONS				
<p>Frame Materials: Main frame - 2x4" 11-gauge 120 wall oval tubular steel with a combination of 2" round and other 11-gauge tubular steel</p> <p>Welds: All welded construction conforming with all Structural Welding Code-Steel Standards and Specifications</p> <p>Padding: High density 1" thick 3 lbs. rebond urethane foam glued to 1" industrial plywood backing, trimmed and formed to exact fit</p> <p>Cabels & Belts: Cable driven units - USA-Made/Certified 3/16" and 1/4" EXERFLEX PRO® high performance fitness cable rated at 4200 lbs. tensile strength. Belt driven units: reinforced Kevlar® belts, rated at 4400 lbs. tensile strength</p> <p>Guide Rods: 3/4" solid steel 1045 (tgp) highly polished hard chrome finish</p> <p>Finish: Powder coat finish baked at 400°F and carefully monitored to ensure complete curing</p> <p>Frame Colors: Custom two tone finish offers choice of six primary colors combined with Charcoal Texture accents. Custom colors available, please inquire with your sales representative</p> <p>Upholstery: Premium Bolta Sport vinyl with PreFixx, formulated to resist bacteria, stains, mildew, oil and UV stabilized pigments. Meets most flammability test requirements. All upholsteries are double-stitched with "hidden" borders. Bolta Sport color swatches are available upon request. Sixteen standard colors. Custom colors are available - please inquire with your sales representative</p>				
<p>Adjustment Pins: 1/2" and 5/8" push-pull spring loaded solid steel adjustment pins with ultimate load of 9040 lbs. and 46042 psi sheer strength</p> <p>Bearings: 1" solid stainless steel pivot axles with non-friction 2" sealed bearings (load rating of 2400 lbs.) internally encased on primary pivots, and oil-impregnated bronze bushings on all secondary pivots</p> <p>Pulleys: Combination wide groove fiberglass reinforced nylon pulleys on belt-driven system and solid aluminum pulleys on cable units</p> <p>Cams: Charcoal Texture powder coat solid aluminum variable resistance cam designed specifically for each machine</p> <p>Fasteners: All frame bolts and nuts are 3/8" and 1/2" blue zinc plated grade 8 and up. Meets ANSI specifications</p> <p>Custom Stabilizer Feet: Heavy-duty molded rubber base feet insure stability, prevent equipment movement, and may be bolted to the floor</p> <p>Selector Weight Pins: Weight pins are solid steel, magnetic with ball-end to ensure a tight connection and secure fit. Coiled lanyard helps prevent pin removal and loss</p> <p>Weight Stack: 150 lbs. steel weight stack with add-on weight system. (Option: 200 lbs.)</p> <p>Warranty: 10 years frame/welds/cams/weight plates, 5 years parts, 6 months upholstery</p>				