

BENCHES & RACKS

FLAT-INCLINE-DECLINE UTILITY BENCH

BOC-F605



- Built for commercial use, rated 1,500 lbs., tested at 3000 lbs.
- Stylish and durable pads fully wrapped in double stitched industrial grade vinyl
- 3 Point stance maintains an extremely solid and stable platform on all surfaces
- Non-slip rubber soles keep the bench in position
- Integrated lift handle and transport wheels for easy maneuvering
- 7 Positions: flat, 1 decline, and 5 incline
- Ladder catch design for quick, easy adjustment
- Space saving compact design



Weight Capacity	Width	Length	Height
1,500 lbs. (3,000 in a flat position)	21"	50"	19.5" (in flat position)

FEATURES AND SPECIFICATIONS

Construction: 2" X 3", heavy-gauge steel tubing

Oil Impregnated Bushings: Located at all pivot points

Metal Caps: Rubber soles on the front and rear leg

Upholstery: 2" thick high-density foam, then covered in double-stitched industrial grade vinyl. Upholstered back covers

7 Positions: Flat, 1 Decline, and 5 Incline : (-20°, 0°, 15°, 30°, 45°, 60°, 85°)

Weight Capacity: 1,500 lbs. tested to 3,000 lbs. in flat position without fail

Warranty: 10 years frame, 2 years parts, 6 months wear items