## key features & benefits

▼ Powerful 3.5 HP, AC motor



 Intuitive LED with dual speed and incline toggle controls, audio input, speakers, USB port, reading rack/tablet holder and cup holders



- Simple design makes the M6 Standard treadmill easier and more efficient to assemble, service and relocate
- Contact and wireless heart-rate sensors are compatible with a variety of industry-leading monitors
- Low step-on height and rubber foot grips
- ✓ 60" x 20" premium lubricant-infused low-maintenance running belt with <u>1" reversible phenolic deck</u>



- More than 20 exercise programs and integrated 2-speed personal fan
- Illuminated power-on switch with quick-connect safety clip
- The Smooth Deck Shock Absorption System with urethane suspension delivers a stable and flexible running surface designed to provide the ultimate comfort, reducing stress on knees and joints
- Zinc-dipped anti-corrosion coating for superior rust protection





## M6 STANDARD TREADMILL CIR-TM6000AC-C

Affordability meets durability in the M6 Standard Treadmill. Featuring high quality components on a space-saving frame. This treadmill is built for unparalleled reliability and efficiency.



## technical specs

Product Weight: 302 lbs.	<b>Running Surface:</b> 60" x 20		Width: 36"	Length: 78"	Height: 57"	
Motor: 3.5 HP, AC		heart-rate sensors				
Electrical: 120V, 20 amp dedicated NEMA 5-20			Display: 8 x 16 dot matrix console with			
Certification: UL, CSA, CE & EU MEPS		message window + HR status bar				
Rollers: 2.75"		<b>Display Feedback:</b> Time, distance, heart-rate, calories, speed, incline, calories/hour, pace				
Step-On Height: 7"			Programs: 20 programs, 1 target, 3 HRC,			
Belt: Premium Habisit™ lubricant-infused low maintenance running belt		1 fitness test, 2 custom <b>Keypad:</b> Teflon keypad TPU lasts 25% longer				
						Deck: 60" x 20" running surface, with
1" reversible phenolic deck		Standard Features: Hand pulse, fan, heart-rate receiver chest belt compatible, 4 quick keys for both speed & incline & reading rack/tablet holder Warranty: 10 years frame, 5 years motor & parts, 1 year wearable items, 1 year labor in light commercial applications (up to 6 hours				
Speed Range: 0.5 - 12.5 MPH						
Incline Range: 0 - 15% incline User Weight: 400 lbs. Transport Wheels: Easy-to-move with front- mounted dual wheels without elevating						

mounted dual wheels without elevating **Frame:** Zinc-dipped, anti-corrosion coated heavy gauge steel

Heart Rate Monitoring: Contact & telemetric

**Warranty:** 10 years frame, 5 years motor & parts, 1 year wearable items, 1 year labor in light commercial applications (up to 6 hours of daily use). Any use of this product in a duepaying facility or facility exceeding 6 hours of daily use may void the warranty.





