TRUE

400 TREADMILL

The C400 Treadmill provides your commercial facility reliable performance and a high-quality experience with patented features like HRC Heart Rate Control® and TRUE'S low-impact Soft System®. In addition, the C400 is the ideal choice for rehabilitation use at health and medical facilities with a low speed of only .2 mph. A variety of console options provide the technology, features, and asset management needed for your facility.



FEATURES

- Minimum Speed: 0.2 MPH (0.3 KPH)
- Optional medical handrails
- Patented HRC Cruise Control® and Soft System® deck
- Multiple console options available

SPECIFICATIONS

DIMENSIONS (L X W X H)

79" x 31.5" x 62" / 200.66 cm x 80.01 cm x 157.48 cm

SPEED

0.2 to 12.0 MPH / 0.3 to 19 KPH

INCLINE/DECLINE LEVELS

0% to 15%

PRODUCT WEIGHT

349 lbs / 158.3 kg

COLOR

Charcoal/Black



CONSOLE OPTIONS



ENVISION



ENVISION WITH COMPASS **ENVISION 9**



EMERGE



IGNITE

400 SERIES



C400 TREADMILL

| TECHNICAL SPECIFICATIONS | Power Source | 120V/20A (NEMA 5-20R receptacle) 230V/15A |
|-----------------------------|--------------------------------|---|
| | Cord Length | 230V/15A (NEMA 6-15R receptacle) |
| | Drive Motor | TRUE 4HP Max Drive AC motor |
| | Power Factor Correction (PFC) | Standard |
| | Incline Motor | 1,200 lbs. of thrust |
| | Speed Sensor | Optical |
| | Deck | 1" / 2.54 cm Medium Density Fiberboard |
| | Reversible Deck | Standard |
| | Belt | Lubricant Infused Siegling Multi-Ply with PVC Coating |
| | Rollers | 3" / 8 cm w/ Shielded Bearings |
| | Impact System | True Soft System® |
| | Frame Construction | Robotically Welded Heavy-Gauge Steel |
| | Lubrication | Silax |
| | Speed Range | 0.2 to 12.0 MPH / 0.3 to 19 KPH |
| | Incline/Decline Range | 0% to 15% |
| | Quick Access Control | Speed, Incline, Start and Stop on Quick Access Point |
| | Handrail Design | Extended Handrails with Rubber, Moisture-Resistant Grips |
| | Contact Heart Rate Monitoring | Yes |
| | Wireless Heart Rate Monitoring | Polar® |
| AVAILABLE CONSOLES | | Envision, Envision with Compass, Envision 9 , Emerge, Ignite |
| ASSET TRACKING | | EcoFit Compatible |
| SAFETY | Safety Clip | Removable |
| | Extended Handrails | Standard |
| | Large Straddle Covers | Standard |
| | User Detection | User Present Detection™ |
| REGULATORY APPROVALS | | ETL UL1647, CSA, CE, EN957, (ISO 20957), FCC |
| EXTRAS | Accessories | Water Bottle Holder (2), Accessory Tray, Over Molded Reading Rack/Tablet Holder, Optional Medical Handrails |
| PHYSICAL SPECIFICATIONS | Footprint | 79" L x 31.5" W x 62" H / 200.66 cm x 80.01 cm x 157.48 cm |
| | Running Surface | 60" L x 22" W / 1524 cm x 55.88 cm |
| | Machine Weight | 349 lbs / 158.3 kg |
| | Shipping Weight | 424 lbs / 192.3 kg |
| | Maximum User Weight | 400 lbs / 181.4 kg |
| | Step-Up Height | 6.5" / 16.51 cm |
| | Portability | 2 Front Transport Wheels |
| WARRANTY | Warranty Type | Commercial (non-dues paying facilities with less than 8 hours of usage per day) |
| | Frame | Lifetime |
| | Motor | 5 Years |
| | Parts | 5 Years (Envision ¹⁶ Console is 3 years) |
| | Labor | 2 Years |
| | | |

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.



