# TRUE

### 900 TREADMILL

The C900 Treadmill combines TRUE's newest technology and performance advancements with the dependable quality and low cost of ownership your facility demands. Backed by TRUE'S premium warranty, the C900 provides runners a high-end experience with the largest running surface in the industry, a speed range up to 17 mph, and TRUE's low-impact Soft System® and HRC Heart Rate Control®. Multiple console options provide customizable features, technology, and asset management capabilities for enhanced user engagement.



- Largest Running Surface in the Industry
- 17.0 MPH (27 KPH) Max speed with 18% Max incline
- HRC Cruise Control® and Soft System® deck
- Reversible Deck

#### **SPECIFICATIONS**

#### **DIMENSIONS** (L X W X H)

84" x 34.5" x 60.5" / 213.36 cm x 87.63 cm x 153.67 cm

#### **SPEED**

0.5 to 17.0 MPH / 0.8 to 27 KPH

#### **INCLINE/DECLINE LEVELS**

0% to 18% (-3% to 18% with Decline Kit)

#### **PRODUCT WEIGHT**

450 lbs / 204 kg

#### COLOR

Charcoal/Black

#### **CONSOLE OPTIONS**



**ENVISION II** 16" Touchscreen



**ENVISION II** 9" Touchscreen



SHOWRUNNER II 16" Integrated LCD



EMERGE II LED Console



IGNITE II LED Console





## 900 SERIES



#### C900 TREADMILL

JOOO INLADMILL		
TECHNICAL SPECIFICATIONS	Power Source	120V/20A (NEMA 5-20R receptacle) 230V/15A
	Cord Length	12' / 3.7 M
	Drive Motor	5 HP AC Self-Cooling Max Drive
	Motor Controller	PFC
	Incline Motor	1,200 lbs. of thrust
	Speed Sensor	Optical
	Deck	Reversible 1" / 2.54 cm Medium Density Fiberboard
	Reversible Deck	Standard
	Belt	Maintenance free, low-amp draw pre-waxed Medex deck and TPU belt system
	Rollers	3" / 8 cm w/ Shielded Bearings
	Impact System	True Soft System®
	Frame Construction	Robotically Welded Heavy-Gauge Steel
	Lubrication	Silax
	Speed Range	0.5 to 17.0 MPH / 0.8 to 27 KPH
	Incline/Decline Range	0% to 18% (-3% to 18% with Decline)
	Quick Access Control	Speed and Incline on Hand Grips with Start and Stop on Quick Access Point
	Handrail Design	Extended Handrails with Molded Rubber, Moisture-Resistant Grips
	Contact Heart Rate Monitoring	Yes
	Wireless Heart Rate Monitoring	Polar® Compatible
AVAILABLE CONSOLES		Envision II 16", Envision II 9", ShowRunner II, Emerge II, Ignite II
ASSET TRACKING		EcoFit Compatible
SAFETY	Safety Clip	Standard/Non-Removable
	Extended Handrails	Standard
	Large Straddle Covers	Standard
	User Detection	Person Present Detection
REGULATORY APPROVALS		ETL UL1647, CSA, CE, EN957, (ISO 20957), FCC
EXTRAS	Accessories	Water Bottle Holder (2), Accessory Tray, Over Molded Reading Rack/Tablet Holder, Power Cord Management, Optional Medical Rails, Optional Decline Feet Kit
PHYSICAL SPECIFICATIONS ————————————————————————————————————	Footprint	84" L x 34.5" W x 60.5" H / 213.36 cm x 87.63 cm x 153.67 cm
	Footprint with Decline	84" L x 34.5" W x 62.5" H / 213.36 cm x 87.63 cm x 158.75 cm
	Running Surface	62" L x 23" W / 157.4 cm x 58.4 cm
	Machine Weight	450 lbs / 204 kg
	Shipping Weight	489 lbs / 222.8 kg
	Maximum User Weight	500 lbs / 226.7 kg
	Step-Up Height	7" / 17.7 cm ( 9" / 22.86 cm with Optional Decline)
	Portability	2 Front Transport Wheels
WARRANTY	Warranty Type	Commercial (all dues paying facilities, regardless of usage)
	Frame	Lifetime
	Motor	5 Years
	Parts	3 Years
	Labor	3 Years
	arranties outside the U.S. and	Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.



hotelfitness.com | 800.291.0403 info@hotelfitness.com