

200 TREADMILL

The 200 Treadmill provides your commercial facility reliable performance and a high-quality experience with features like HRC Heart Rate Control® and TRUE'S low-impact Soft System®. The 200 treadmill is the ideal choice for rehabilitation use at health and medical facilities with space-efficiency and low profile design in mind.



TWO WINDOW LCD DISPLAY

Standard two window LCD display console featuring 12-15 programs, HRC Heart Rate Control® cruise control, CSAFE power.

FEATURES

- Minimum Speed: 0.5 MPH (0.3 KPH)
- Extended handrails
- HRC Cruise Control®
- TRUE Soft System® deck

SPECIFICATIONS

DIMENSIONS (L X W X H)

83.5" x 32" x 60.5" / 212.09 cm x 81.2 cm x 153.67 cm

SPEED

0.2 to 12.0 MPH / 0.3 to 19 KPH

INCLINE/DECLINE LEVELS

0% to 15%


PRODUCT WEIGHT

349 lbs / 158.3 kg

COLOR

Silver

Impact system:
TRUE Soft System®



CONSOLE OPTIONS



TWO WINDOW LCD DISPLAY

Standard two window LCD display console featuring 12-15 programs, HRC Heart Rate Control® cruise control, CSAFE power.

200 SERIES



CS200 TREADMILL

TECHNICAL SPECIFICATIONS	Power Source	110V/15A (NEMA 5-20R receptacle)	
	Cord Length	10' / 3.0 M	
	Drive Motor	4 HP AC Endura-Drive	
	Incline Motor	1,000 lbs. of thrust	
	Speed Sensor	Optical	
	Deck	1" / 2.54 cm Medium Density Fiberboard	
	Belt	Lubricant Infused Siegling Multi-Ply with PVC Coating	
	Rollers	3" / 8 cm w/ Sealed Bearings	
	Impact System	True Soft System®	
	Frame Construction	Robotically Welded Heavy-Gauge Steel	
	Lubrication	Silax	
	Speed Range	0.5 to 12.0 MPH / 0.8 to 19.3 KMH	
	Incline/Decline Range	0% to 15%	
	Quick Access Control	Speed, Incline, Start and Stop on Quick Access Point	
	Handrail Design	Extended Handrails with Molded Rubber, Moisture-Resistant Grips	
	Contact Heart Rate Monitoring	Yes	
	Wireless Heart Rate Monitoring	Polar® Compatible	
	CONSOLE	Display	LCD
		Programs	12
		HRC Workouts	1
HRC Cruise Control		Standard	
CSAFE Power		Standard	
Diagnostic		Standard	
SAFETY	Safety Clip	Standard	
	Extended Handrails	Standard	
	Large Straddle Covers	Standard	
REGULATORY APPROVALS	ETL, UL1647, CSA, (CE for 220 v)		
PHYSICAL SPECIFICATIONS	Footprint	83.5" L x 32" W x 60.5" H / 212.09 cm x 81.2 cm x 153.67 cm	
	Running Surface	60" L x 22" W / 152.4 cm x 55.88 cm	
	Machine Weight	349 lbs / 158.3 kg	
	Shipping Weight	424 lbs / 192.3 kg	
	Maximum User Weight	350 lbs / 158.7 kg	
	Step-Up Height	6.25" / 15.88 cm	
	Portability	2 Front Transport Wheels	
WARRANTY	Warranty Type	Commercial (non-dues paying facilities with less than 8 hours of usage per day)	
	Frame	Lifetime	
	Motor	5 Years	
	Parts	5 Years	
	Labor	1 Year	

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.



hotelfitness.com | 800.291.0403
info@hotelfitness.com